





NOZZLE
Diameter 8 · 18 mm



1,45 Kg



**FULL & PART CIRCLE
MODEL**



P/24-S

PART CIRCLE DYNAMIC SPRINKLER
EQUIPPED WITH TWO NOZZLES: THE MAIN
ONE ENSURES THE JET LENGTH AND
THE SECONDARY ONE TRIGGERS THE ROCKER ARM
THE MAIN NOZZLE IS EQUIPPED WITH AN
ADJUSTABLE JET-BREAKER THAT ENSURES
UNIFORM DISTRIBUTION OF WATER IN
THE VICINITY OF THE SPRINKLER
SUITABLE FOR THE IRRIGATION OF PARKS,
ORCHARDS, CITRUS GROVES, VEGETABLES
AND FOR DUST SUPPRESSION
1"1/2 FEMALE SCREW CONNECTION
UPON REQUEST, 1"1/4 FEMALE SCREW CONNECTION.
PLASTIC INTERCHANGEABLE NOZZLES
MATERIALS USED: PA, ALUMINIUM, BRASS,
STAINLESS STEEL, NBR, TEFLON

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
12x7	2	22	165	8
12x7	3	25	198	7,60
12x7	4	27	221	7
14x7	2	23	218	9,1
14x7	3	27	264	8,9
14x7	4	29	305	8,6
16x7	2	28	321	11,3
16x7	3	30	370	10,80
16x7	4	32	401	10,20

