




NOZZLE
Diameter 8 • 18 mm

**FULL & PART CIRCLE
MODEL**




2,275 Kg

27,5 cm



37,5 cm



P/25-S

PART CIRCLE DYNAMIC SPRINKLER
EQUIPPED WITH TWO NOZZLES: THE MAIN ONE
ENSURES THE JET LENGTH AND THE SECONDARY
ONE TRIGGERS THE ROCKER ARM
THE MAIN NOZZLE IS EQUIPPED WITH AN ADJUSTABLE
JET-BREAKER THAT ENSURES UNIFORM DISTRIBUTION
OF WATER IN THE VICINITY OF THE SPRINKLER
SUITABLE FOR THE IRRIGATION OF VEGETABLES,
PARKS, FOOTBALL FIELDS/GOLF COURSES AND
FOR DUST SUPPRESSION
2" FEMALE SCREW CONNECTION
PLASTIC INTERCHANGEABLE NOZZLES
MATERIALS USED: PA, ALUMINIUM, BRASS,
STAINLESS STEEL, NBR, TEFLON

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
12x8,5	3	27	294	9
12x8,5	4	29	315	8,80
12x8,5	5	31	336	8,6
14x8,5	3	28	324	10,8
14x8,5	4	30	348	10,5
14x8,5	5	32	390	10,3
16x8,5	3	32	468	11,5
16x8,5	4	34	534	11,10
16x8,5	5	36	588	10,60

