





NOZZLE
Diameter 3 - 4,5 mm

**FULL & PART CIRCLE
MODEL**



0,185 Kg

12 cm



10,5 cm

P/5-S

SINGLE-JET PART CIRCLE DYNAMIC SPRINKLER
LIFTING THE TRIP LEVER, THE SPRINKLER BECOMES
A FULL CIRCLE MODEL
EQUIPPED WITH AN ADJUSTABLE JET-BREAKER THAT
ENSURES UNIFORM DISTRIBUTION OF WATER
IN THE VICINITY OF THE SPRINKLER
SUITABLE FOR THE IRRIGATION OF GARDENS,
GREENHOUSES, VINEYARDS AND ORCHARDS
1/2" MALE SCREW CONNECTION
BRASS INTERCHANGEABLE NOZZLES
MATERIALS USED: PA, ZAMAK, BRASS,
STAINLESS STEEL, NBR, TEFLON

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
3	1,5	9	6,6	1,54
3	2	10	7,8	1,47
3	3	11,5	9,6	1,38
3,5	1,5	9,5	8,5	1,65
3,5	2	10,5	10	1,54
3,5	3	12	12	1,49
4	1,5	10	9	1,75
4	2	11	11	1,70
4	3	12,5	13	1,60

