





NOZZLE
Diameter 16 - 22 mm



5,5 Kg



**FULL & PART CIRCLE
MODEL**



P/50

DYNAMIC TURBINE GUN
BOTH FULL CIRCLE AND PART CIRCLE FUNCTIONING
EQUIPPED WITH TWO NOZZLES: THE MAIN ONE
ENSURES THE JET LENGTH AND THE SECONDARY
ONE TRIGGERS THE TURBINE
THE MOVEMENT IS UNIFORM AND ENSURES EXCELLENT
DISTRIBUTION OF WATER IN THE VICINITY OF THE GUN
THE MAIN NOZZLE IS EQUIPPED WITH AN
ADJUSTABLE JET-BREAKER
A PRECISE SECTOR ADJUSTMENT CAN BE MANUALLY
DONE BY THE OPERATOR IN ABSOLUTE SAFETY
SUITABLE FOR STATIONARY INSTALLATIONS
2" FEMALE SCREW CONNECTION

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
16x7	2	27	302	8,50
16x7	3	29	369	8,80
16x7	4	32	426	7,90
18x7	3	33	454	8,50
18x7	4	36	531	8,30
18x7	5	39	588	7,80
20x7	4	38	633	8,60
20x7	5	42	684	7,80
20x7	6	45	773	7,60

**BRASS INTERCHANGEABLE NOZZLES FOR THE MAIN WATER OUTLET
AND PLASTIC ONES FOR THE SECONDARY HOLE**
MATERIALS USED: PA, ALUMINIUM, BRASS, STAINLESS STEEL, TEFLON

