





NOZZLE
Cap / Diameter 4,75 · 10 mm

**FULL CIRCLE
MODEL**



0,550 Kg



PSC/15 4°

UNDERTREE DOUBLE-JET FULL CIRCLE DYNAMIC
SPRINKLER
TRAJECTORY ANGLE: 4°
EQUIPPED WITH AN ADJUSTABLE JET-BREAKER
THAT ENSURES UNIFORM DISTRIBUTION OF WATER
SUITABLE FOR THE IRRIGATION OF GARDENS, PARKS,
ORCHARDS AND VEGETABLES
PARTICULARLY SUITABLE FOR IRRIGATION IN
HIGH-WIND AREAS
1" FEMALE SCREW CONNECTION
PLASTIC INTERCHANGEABLE NOZZLES
MATERIALS USED: PA, ZAMAK, BRASS,
STAINLESS STEEL, NBR, TEFLON

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
4,75x5,5	2	12,5	45	5,51
4,75x5,5	3	14,5	54	5,18
4,75x5,5	4	15,5	66	5,25
4,75x6,25	2	13,5	54	5,66
4,75x6,25	3	14,5	66	6
4,75x6,25	4	15,5	75	5,96
4,75x7	2	14	66	6,43
4,75x7	3	15	78	6,62
4,75x7	4	16	90	6,72

