





NOZZLE
Diameter 6 • 12 mm

**FULL & PART CIRCLE
MODEL**



1,23 Kg

23 cm



28 cm

PSC/22 9°-S

UNDERTREE SINGLE-JET PART CIRCLE
DYNAMIC SPRINKLER
TRAJECTORY ANGLE: 9°
UPON REQUEST, THE FULL CIRCLE MODEL
IS AVAILABLE TOO
EQUIPPED WITH AN ADJUSTABLE JET-BREAKER
THAT ENSURES UNIFORM DISTRIBUTION OF WATER
SUITABLE FOR THE IRRIGATION OF PARKS, ORCHARDS,
CITRUS GROVES, VEGETABLES AND FOR
DUST SUPPRESSION
PARTICULARLY SUITABLE FOR IRRIGATION
IN HIGH-WIND AREAS
1"1/4 FEMALE SCREW CONNECTION.
UPON REQUEST, 1"1/2 FEMALE SCREW CONNECTION

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
6	2	10	42	8,02
6	3	11	54	8,52
6	4	12	60	7,94
8	2	13	54	6,27
8	3	15	60	5,79
8	4	16,5	78	5,47
10	2	14	90	8,77
10	3	16,5	108	7,58
10	4	18	120	7,07

PLASTIC INTERCHANGEABLE NOZZLES
MATERIALS USED: PA, ALUMINIUM, BRASS, STAINLESS STEEL,
NBR, TEFLON

