



NOZZLE
Diameter 16 • 22 mm



9,4 Kg


50 cm



100 cm



**FULL & PART CIRCLE
MODEL**



PVR/50

DYNAMIC GUN WITH ROCKER ARM.
BOTH FULL CIRCLE AND PART CIRCLE FUNCTIONING.
A PRECISE SECTOR ADJUSTMENT CAN BE MANUALLY
DONE BY THE OPERATOR IN ABSOLUTE SAFETY.
23° TRAJECTORY ANGLE GUARANTEES THE MAXIMUM
JET LENGTH POSSIBLE IN ANY WORK CONDITION.
ADJUSTABLE CLUTCH TO OPTIMIZE THE GUN
PERFORMANCES AT LOW AND HIGH PRESSURES.
SUITABLE FOR ANY MOBILE OR STATIONARY
INSTALLATION, PIVOTS AND IN PARTICULAR
SELF-PROPELLED MACHINES.
THE MOVEMENT PRODUCED DURING ITS FUNCTIONING
DOES NOT DEVIATE THE TROLLEY ESPECIALLY ON SLOPING
TERRAINS AND ENSURES PERFECT STABILITY ON
FIXED INSTALLATIONS.
2" FEMALE SCREW CONNECTION.
BRASS INTERCHANGEABLE NOZZLE.
MATERIALS USED: PA, ALUMINIUM, BRASS,
STAINLESS STEEL, TEFLON

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
16	3	32	283	5,10
16	4	36	320	4,70
16	5	40	370	4,40
18	3	35	360	6,10
18	4	39	415	5,60
18	5	42	462	5,10
20	4	41	515	6,20
20	5	44	572	5,70
20	6	48	625	5,30

