




 12 Kg



PVR/70

DYNAMIC GUN WITH ROCKER ARM
BOTH FULL CIRCLE AND PART CIRCLE FUNCTIONIN.
A PRECISE SECTOR ADJUSTMENT CAN BE MANUALLY
DONE BY THE OPERATOR IN ABSOLUTE SAFETY
23° TRAJECTORY ANGLE GUARANTEES THE MAXIMUM
JET LENGTH POSSIBLE IN ANY WORK CONDITION
ADJUSTABLE CLUTCH TO OPTIMIZE THE GUN
PERFORMANCES AT LOW AND HIGH PRESSURES
SUITABLE FOR ANY MOBILE OR STATIONARY
INSTALLATION, PIVOTS AND IN PARTICULAR
SELF-PROPELLED MACHINES
THE MOVEMENT PRODUCED DURING ITS FUNCTIONING
DOES NOT DEVIATE THE TROLLEY ESPECIALLY ON
SLOPING TERRAIN AND ENSURES PERFECT STABILITY
ON FIXED INSTALLATIONS
6-HOLE FLANGED SCREW CONNECTION
PLASTIC INTERCHANGEABLE NOZZLE
MATERIALS USED: PA, ALUMINIUM, BRASS,
STAINLESS STEEL, TEFLON

NOZZLE Ø	PRESSURE ATM	JET LENGHT MT	DISCHARGE L/MIN	RAINFALL MM/H
24	4	45	737	7,10
24	5	49	825	6,60
24	6	53	905	6,20
28	4	53	1125	7,70
28	5	57	1230	7,50
28	6	60	1328	7,30
32	5	58	1458	8,70
32	6	62	1595	8,60
32	7	65	1715	8,40

